

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

1 Identification

Product identifier
Trade name: Osmo Maintenance Oil

Other means of identification
Article number: 3079 Clear Matt, 3081 Clear Satin, 3440 White Transparent

Application of the substance
/ the mixture Maintenance product

Details of the supplier of the safety data sheet
Manufacturer/Supplier:
Supplier

Osmo Wood and Colour Canada Ltd.
 420 Thompson Drive - Unit 2
 N1T 2K8 Cambridge, ON
 Canada
 Tel: +1-844-OSMOCAN
 E-mail: info@osmo.ca

Manufacturer

Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf
 Germany

Information department:

Product safety department
 Tel.: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

Emergency telephone number:

24h-Emergency Phone Number:
 For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or
 Night within USA and Canada 1-800-424-9300
 Outside USA and Canada 001-703-527-3887 (CCN 16475)

2 Hazard identification

Classification of the substance or mixture

Flammable liquids – Category 4 H227 Combustible liquid.

Additional information: For the wording of the listed hazard phrases refer to section 16.

Label elements
Hazard pictograms

Void

Signal word

Warning

Hazard statements

H227 Combustible liquid.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat. No smoking.

(Contd. on page 2)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 1)

P262 Do not get in eyes, on skin, or on clothing.
 P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
 P403 Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with national regulations.

Information pertaining to particular dangers for man and environment:
Classification system:

NFPA ratings (scale 0 - 4) Health = 0
 Fire = 2
 Reactivity = 0

HMIS-ratings (scale 0 - 4) Health = 0
 Fire = 2
 Reactivity = 0




Other hazards CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.
 Always wear a dust mask when sanding.
 Observe the general safety regulations when handling chemicals.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

	Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics  Aspiration hazard – Category 1, H304	10-30% w/w *
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2%  Aspiration hazard – Category 1, H304; Flammable liquids – Category 4, H227	10-30% w/w *
CAS: 34590-94-8	Dipropylene glycol monomethyl ether  Flammable liquids – Category 4, H227	1-5% w/w *

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

Description of first aid measures

General information: Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 2)

After skin contact: Immediately wash with water and soap and rinse thoroughly.
If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed Dizziness

Indication of any immediate medical attention and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
carbon dioxide (CO₂)

Advice for firefighters
Protective equipment: Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
General measures for chemical fires.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
Keep away from ignition sources
Wear protective clothing.

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training.

For emergency responders Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 3)

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the collected material according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about protection

against explosions and fires: Keep respiratory protective device available.

Handling:

Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:

10

Specific end use(s)

No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 4)

8 Exposure controls/ Personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

EL	Short-term value: 150 ppm Long-term value: 100 ppm Skin
EV	Short-term value: 910 mg/m ³ , 150 ppm Long-term value: 605 mg/m ³ , 100 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and

hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing.
 Do not inhale gases / fumes / aerosols.
 The usual precautionary measures for handling chemicals should be followed.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 See Section 7 for information on safe handling.

Breathing equipment:

Use suitable respiratory protective device only when aerosol or mist is formed.
 Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
 Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Protection of hands:

Protective gloves and protective skin cream
 To avoid skin problems reduce the wearing of gloves to the required minimum.
 Protective gloves
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

(Contd. on page 6)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 5)

Penetration time of glove material

checked prior to the application.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Physical state

Liquid

Color:

According to product specification

Odor:

Characteristic

Odor threshold:

Not determined.

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

Undetermined.

Flammability:

Not applicable.

Explosion limits:
Lower:

Not determined.

Upper:

Not determined.

Flash point:

>60 °C (DIN EN ISO 2719)

Auto igniting:

210 °C

Decomposition temperature:

Not determined.

pH-value:

Mixture is non-polar/aprotic.

Viscosity:
Dynamic:

Not determined.

Solubility in / Miscibility with
Water:

Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):

Not determined.

Vapor pressure:

Not determined.

(Contd. on page 7)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 6)

Vapor pressure:**Density at 20 °C:**0.85-0.95 g/cm³ (DIN 51757)**Relative density**

Not determined.

Particle characteristics

Not applicable.

Other information**Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

Change in condition**Evaporation rate**

Not determined.

10 Stability and reactivity

Reactivity

No further relevant information available.

Chemical stability**Thermal decomposition /****conditions to be avoided:**

No decomposition if used and stored according to specifications.

Possibility of hazardous**reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials:

No further relevant information available.

Hazardous decomposition**products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

Formation of toxic gases is possible during heating or in case of fire.

Additional information:

CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

(Contd. on page 8)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 7)

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

CAS: 246538-78-3 Kohlenwasserstoffe, C11-C13, Isoalkane

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Inhalative	LC50 / 4h	>5 mg/l (rat)

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat) 13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye: No irritating effect.

Based on available data, the classification criteria are not met.

Sensitization: Sensitizing effect by skin contact is possible with prolonged exposure.

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

CAS: 7631-86-9	silicon dioxide, chemically prepared	3
----------------	--------------------------------------	---

NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 8)

12 Ecological information

Toxicity

Aquatic toxicity:

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h >1,000 mg/l (algae)

LC50 / 96h >1,000 mg/l (fish)

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h 70.2 mg/l

1,919 mg/l (Daphnia magna)

EC50/ 72h >969 mg/l (algae)

LC50 / 96h >10,000 mg/l (aquatic vertebrates - in vivo)

>1,000 mg/l (fish)

5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

LC50 / 48h 1,919 mg/l (daphnia)

10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects

Behavior in sewage processing plants:

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

EC50/ 96h 969 mg/l (algae)

Additional ecological information:

General notes: Water hazard class 2 (Self-assessment): hazardous for water
 Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Disposal must be made according to official regulations.

(Contd. on page 10)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 9)

Uncleaned packagings:**Recommendation:**

Disposal must be made according to official regulations.

Recommended cleansing agent:

Solvent naphtha

Osmo Brush Cleaner and Thinner

14 Transport information

UN-Number**DOT/TDG, ADR, ADN, IMDG, IATA**

Not applicable

UN proper shipping name**DOT/TDG, ADR, ADN, IMDG, IATA**

Not applicable

Transport hazard class(es)**DOT/TDG, ADR, ADN, IMDG, IATA****Class**

Not applicable

Packing group**DOT/TDG, ADR, IMDG, IATA**

Not applicable

Environmental hazards:**Marine pollutant:**

No

Transport in bulk according to Annex II of**MARPOL73/78 and the IBC Code**

Not applicable.

Special precautions for user

Not applicable.

UN "Model Regulation":

Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture**Sara****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances**Control Act):**

All ingredients are listed.

(Contd. on page 11)

Safety Data Sheet

according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 10)

Canadian substance listings:
Canadian Domestic Substances List (DSL)

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

CAS: 7631-86-9 silicon dioxide, chemically prepared

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

Void

Signal word

Warning

Hazard statements

H227 Combustible liquid.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat. No smoking.

P262 Do not get in eyes, on skin, or on clothing.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Version number of previous
version:

7.0

Date of preparation

11/19/2025

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)

(Contd. on page 12)

Safety Data Sheet
according to HPR, Schedule 1

Date of issue 11/19/2025

Version number 8.0

Revision: 11/19/2025

Trade name: Osmo Maintenance Oil

(Contd. of page 11)

Sources

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ESIS : European chemical Substances Information System

ECHA Portal

Safety data sheets from raw material suppliers

*** Data compared to the
previous version altered.**

Additions, deletions, revisions